



Tile pure

Data sheets



Tile Pure

It is a high-quality, ready-mixed, cement-based, waterproof grout that is quick and easy to use and resistant to all weather and climatic conditions, especially in coastal areas. It is used to fill ceramic, marble, and tile joints in walls and floors. It is recommended for use with Pure ceramic and porcelain adhesive products.

Installation

Tile Pure complies with American specifications

ANSI 118.6

Colors

The product is available in gray, white, and multiple colors upon request.

Packaging

Available in 15 kg and 5 kg bags.

Features

- 1- High quality raw material selection and testing, subject to the latest quality control systems.
- 2- Accurate mixing ratio standard.
- 3- Economical and easy to use (requires only money).
- 4- High adhesion strength, crack-free, and highly resistant to various weather factors and conditions.

Free from various types of salts, making it recommended for use in coastal areas.

- 5- Can be used on interior and exterior surfaces.
- 6- Suitable for use in dry and humid areas.
- 7- Non-fading mortar.
- 8- Colorfast and unaffected by sunlight and UV rays.

Technical Specifications

1- Binder: Portland Cement

ASTM C 150

2- Density: 1.3 kg per liter

3- Add 5/6 liters of water to each 20 kg bag of dry product



Tile pure

Data sheets



Tile Pure

It is a high-quality, ready-mixed, cement-based, waterproof grout that is quick and easy to use and resistant to all weather and climatic conditions, especially in coastal areas. It is used to fill ceramic, marble, and tile joints in walls and floors. It is recommended for use with Pure ceramic and porcelain adhesive products.

Installation

Tile Pure complies with American specifications

ANSI 118.6

Colors

The product is available in gray, white, and multiple colors upon request.

Packaging

Available in 15 kg and 5 kg bags.

Features

- 1- High quality raw material selection and testing, subject to the latest quality control systems.
 - 2- Accurate mixing ratio standard.
 - 3- Economical and easy to use (requires only money).
 - 4- High adhesion strength, crack-free, and highly resistant to various weather factors and conditions.
- Free from various types of salts, making it recommended for use in coastal areas.
- 5- Can be used on interior and exterior surfaces.
 - 6- Suitable for use in dry and humid areas.
 - 7- Non-fading mortar.
 - 8- Colorfast and unaffected by sunlight and UV rays.

Technical Specifications

1- Binder: Portland Cement

ASTM C 150

2- Density: 1.3 kg per liter

3- Add 5/6 liters of water to each 20 kg bag of dry product

4- Setting time (24°C): 2 hours

5- Compressive strength: 250 kg/cm² after 28 day